



## Introduction

The IQview™ 802.11a/b/g/n WLAN and Bluetooth Test System is an all-in-one test instrument developed specifically for RF testing of 802.11a/b/g/n WLAN and Bluetooth products. Suitable for development and DVT (Design Verification) environments, the IQview test system integrates a vector signal analyzer (VSA) and a vector signal generator (VSG) into a single instrument.

## Functionality

The IQview test system is expressly designed to test WLAN and Bluetooth products, including network interface cards, access points, and embedded components/modules.

The IQview test system's VSA capability replaces traditional spectrum analyzers and power meters, enabling the user to analyze a device under test's transmitter output and perform true error vector magnitude (EVM) measurements. Designed to receive large input signals without distortion, the IQview test system employs a wide-bandwidth Capture-Once Measure-All approach so that the device under test's transmit signal is sampled and stored in a single measurement for subsequent analysis of all desired parameters resulting in reduced test times.

Similarly, the IQview test system's VSG capability replaces traditional golden units with a test signal source of much higher quality, allowing detailed analysis of the receiver performance of the device under test. The IQview test system is designed to output high-quality test signals over the full expected operating range of a WLAN or Bluetooth receiver.

The IQview test system supports testing in both the 2.4 GHz and 5 GHz frequency bands utilized worldwide for 802.11a/b/g/n and Bluetooth products. Inputs and outputs at both RF and baseband are provided, enabling detailed testing of all aspects of a WLAN product's analog design.



## Features

- Seamless analysis of DSSS (802.11b/g), OFDM (802.11a/g/n) WLAN and Bluetooth (1.0 / 2.0 / 2.1) signals
- Advanced Vector Signal Analyzer (VSA) and Vector Signal Generator (VSG) combined with the capabilities of a power meter and spectrum analyzer in a single instrument
- Operation in both 2.4 GHz and 5 GHz bands
- Baseband analog I/O facilitates product debugging
- High-performance VSA
  - Wide bandwidth (60 MHz)
  - Capture-Once Measure-All operation
  - Graphical and numerical display of measurement results
- High-performance VSG
  - Pre-defined 802.11a/b/g/n and Bluetooth transmit test signals
  - Impairments can be introduced in real-time to the transmit test signal
  - Generation of arbitrary 802.11a/b/g/n waveforms simplified by optional IQwave WLAN Waveform software
- Simple control interfaces
  - IQsignal Signal Analysis Software Suite facilitates signal analysis, signal generation, and debugging
  - LitePoint API supports Visual C/C++ test scripts for use in manufacturing
  - LabVIEW 8.2 and 8.5 libraries for LabVIEW programming

## VSA Performance

Parameters	Specification
Frequency	<ul style="list-style-type: none"> <li>Baseband</li> <li>2400 - 2500 MHz</li> <li>4900 - 6000 MHz</li> </ul>
<b>RF Port</b>	
Input amp level (max)	<ul style="list-style-type: none"> <li>2400 - 2500 MHz: +30 dBm</li> <li>4900 - 6000 MHz: +30 dBm</li> </ul>
<b>Baseband Port</b>	
Input level	<ul style="list-style-type: none"> <li>5-1000 mVrms</li> <li>± 1.5 V peak</li> </ul>

## VSG Performance

Parameters	Specification
Frequency	<ul style="list-style-type: none"> <li>Baseband</li> <li>2400 - 2500 MHz</li> <li>4900 - 6000 MHz</li> </ul>
<b>RF Port</b>	
Output level	<ul style="list-style-type: none"> <li>2400 - 2500 MHz: -95 to 0 dBm</li> <li>4900 - 6000 MHz: -95 to -10 dBm</li> </ul>
<b>Baseband Port</b>	
Output level	<ul style="list-style-type: none"> <li>≤ 1000 mVrms</li> <li>± 1.5 V peak</li> </ul>

## System Requirements

IQsignal Signal Analysis Software Suite; IQdebug Monitor and Control Tool

PC	Intel Pentium processor or higher
Operating system	Microsoft Windows 2000; Windows XP Professional; Windows XP Home Edition
Memory	≥ 128MB of RAM
Disk space	≥ 200MB of available hard disk space
Monitor	At least 1024 x 768 resolution
Connectivity	TCP/IP over 10/100BaseT Ethernet

## Physical & Environmental

Dimensions	450 mm x 100 mm x 500 mm
Weight	8.2 kg
Power consumption	300W max
Operating temperature	0°C to +55°C (68-2-1, 2, 14)
Guaranteed Specification	+20°C to +30°C ambient
Storage temperature	-40°C to +70°C (68-2-1, 2, 14)
Operating humidity	15% to 95% relative humidity, non-condensing (68-2-30)

## Order Code

Order Code	Description
IQV 802-11ABG202	A/B/G 802.11 + Bluetooth

LitePoint Corporation - Corporate Headquarters

575 Maude Court, Sunnyvale, CA 94085 | +1.408.456.5000 | [www.litepoint.com](http://www.litepoint.com) | [sales@litepoint.com](mailto:sales@litepoint.com)

LitePoint and the LitePoint logo, IQview IQflex, IQnxn, and IQmax are registered trademarks and IQsignal, IQwave, IQfact, IQcheck IQdebug, IQmeasure, IQtest, IQexpress, IQturbo, IQultra, IQ2010, TrueChannel, and TrueCable are trademarks of LitePoint Corporation. Microsoft Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries. All trademarks or registered trademarks are owned by their respective owners. The information furnished by LitePoint Corporation is believed to be accurate and reliable. However, no responsibility is assumed by LitePoint for its use. LitePoint reserves the right to change specifications and documentation at any time without notice. © 2010 LitePoint–May 2010

